

# 628

## HIGH PERFORMANCE TROMMEL

The McCloskey 628 Trommel Screener is suited for large heavy-duty applications where production rates can reach 200+ TPH in topsoil and sticky material or 300+ TPH in sand and gravel.

With a 6' diameter screen, the 628 Trommel generates a powerful screening action while the 28' long drum ensures longer time on the screen and the highest quality end product.

McCloskey International is the world's leading trommel manufacturer in pioneering trommel design and innovation. All McCloskey trommels undergo extensive field testing and are continuously improved through customer feedback.

Available as a wheeled mobile unit or hydraulic raise/lower track bogie system and McCloskey provides numerous custom drum and feeder options that are offered to meet each customer's unique requirements.



### OVERSIZE CONVEYOR

Heavy duty oversize 36" conveyor at the end of the trommel offers adjustable speed and stockpile height.



### TEDD PANEL UNIVERSAL DISPLAY

The control panel provides an intuitive, icon-based user interface, which allows all functions to be controlled and monitored.

### CHASSIS

Designed complete with tandem or tri-axle running gear and mounts a larger 320 US gallon diesel fuel tank.



### LARGE DRUM

6 feet in diameter and 28 feet long, with numerous drum and screen options available.

### ADJUSTABLE BRUSHES

User-friendly ground level adjustable brushes for minimal downtime and maximum efficiency.



### RADIAL FINES CONVEYOR

Features a remote controlled radial conveyor with 160° swing and variable discharge height for maximum stockpiling flexibility.

Engine	174 hp (130 kW) Diesel
Transport Height	13' 6" (4.11m)
Transport Length	65' 3" (19.88m)
Transport Width	8' 6" (2.59m)
Weight	59,750 lb (27,100kg)
Radial Stockpile Height	16' 10" (5.13m)
Oversize Stockpile Height	11' 5½" (3.08m)
Drum	6'x28' (1.83mx8.53m)